



r37a

2 CHANNEL TONE AND SPEECH TESTING
CLINICAL AUDIOMETER

PRODUCT SPECIFICATIONS

Please contact Resonance should you have any questions:
support@resonance-audiology.com

GENERAL SPECIFICATIONS

DIMENSIONS AND WEIGHT

- L x W x H: 370x290x180 mm
- Net weight: 3.5 kg
- Body material: Bayblend® self-extinguishing

TEST TYPES

- Pure Tone test, Autothreshold, ABLB, Speech Test, Stenger, DLI, SISI, Bekesy, Tone Decay, MLB, Multifrequency, GAP, DLF (Difference Limen for Frequency)

DISPLAY

- 7" TFT Color display

USER INTERFACE

- Multilingual

PRINTER

- Built-in fast thermal printer with paper width: 112 mm supplied as standard part

REPORTS

- Printed on thermal printer
- .pdf report create directly from the device and stored on USB Pen drive with possibility to add patient data and tests comments via the USB Keyboard (optional)
- Data transfer to PC using Resonance Management Data Suite

DATA TRANSFER TO PC

- Via cable through USB port

COMMUNICATION PORT

- Nr.1 USB host type A
- Nr.1 USB slave type B

WINDOWS® COMPATIBLE SOFTWARE

- Resonance MDS Management Data Suite

POWER

POWER SUPPLY

- 110-240V AC 50/60Hz 40VA
- Fuses: 2 x T 1 A L 250V

CONSUMPTION

- Max current: 0,15A
- Power consumption: 40VA

ENVIRONMENTAL

OPERATING ENVIRONMENT

- Storage: -20° C up to +50° C
- Operating: +15° C up to +35° C
- Humidity: up to 90% (non condensing)
- Ambient pressure: from 700hPa up to 1060hPa

AUDIOMETRY OPERATING SPECIFICATIONS

RANGE

- Frequency range:
 - 125 - 8000 Hz (with DD45)
 - 125 - 12500 Hz (with HDA280)
 - 250 - 8000 Hz (with B71-W)

ACCURACY

- Frequency < 0,5%
- Distortion < 1%
- Attenuator linearity 1dB per 5dB step, max 3dB whole range
- Range stimuli level -10 up to 120 dB HL

TYPE OF SIGNALS

- Pure tone: sine wave 125 to 8KHz signal (to 12,5KHz for HDA280 phones)
- Warble: ± 5% frequency sine wave modulated, modulation: sine wave 5 Hz
- Narrow band noise: 24dB/oct filtered noise
- Speech noise: 1kHz 12dB/oct filtered noise
- White noise
- External signal
- External mike
- Speech material recorded on SD card
- Master Hearing Aid: 1KHz 6, 12, 18 ,24dB High pass filters
- On/Off rise – fall time: 40msec

OUTPUT TRANSDUCERS

- ACR, ACL: 10 ohm DD45 matched pair earphone, (alternatively HDA280 Sennheiser, Insert earphones)
- BC: B71-W Radioear; B81 (optional)
- INSERT: Button receiver
- Free field output: 600 ohm impedance
- Monitor Phone: headset with boom microphone

STIMULUS PRESENTATION MODALITY

- Presentation: Normal, Reverse, Extended (present tone for 1 second from 20dB below the maximum level)
- Modality: Continuous, Pulsed (rate 0,5; 1 and 2 Hz), Alternated (ABLB and MLB - 0,5, 1 and 2 Hz)
- DLI increment levels:
 - 0,1 in steps of 0,1dB up to 1.0dB; 1,5-2-3.4.5 dB
- DLI increment recurrence rates: 0.5Hz, 1Hz, 2Hz
- SISI increment recurrence rates:
 - 0.2Hz, 0.5Hz, random. Time on 300ms
- SISI increment level: 0.25, 0.5, 0.75, 1, 1.5, 2, 3, 4, 5 dB
- Bekesy: mode sweep and fixed; Continuous, Pulsed and LOT; exam duration 30sec and 60sec.

QUALITY SYSTEM

Manufactured, designed, developed and marketed under an ISO 13485, ISO 9001 certified quality system. Medical CE marks and FDA approval

COMPLIANCE/REGULATORY STANDARDS

Designed, tested and manufactured to meet the European and International Standards:

- MDD 93/42/EEC and update 2007/47/CEE: Class IIa (as referred to in Annex IX, rule 10 of said MDD 93/42 EEC)
- Safety: IEC 60601-1, 3rd and 2nd edition, Class 1 Type B
- EMC: IEC 60601-1-2
- Audiometer: to IEC 60645-1; IEC 60645-2 and ANSI S3.6 Type 1A (R37A)

STANDARD ACCESSORIES

- DD45 or HDA280 headset for audiometry testing
- B71W bone conductor
- Insert-Transducer (for bone conductor masking)
- Operator headset with microphone and speaker (talk over and monitor)
- Patient microphone (talk back)
- Internal speaker as monitor use
- Patient response pushbutton
- Built-in fast thermal printer
- 1 roll of thermal paper
- Power supply cable (110 – 220V)
- Device dust cover
- Multilingual Quick User's Handbook
- Pen-drive
- SD-card with Multilanguage speech material
- Resonance® MDS software with NoAH® module included (demo version)

OPTIONALS

- USB external keyboard
- Goose-neck microphone
- Carrying bag
- TDH39 headset
- Pediatric Headset (AC or BC)
- ADC Audiocups Noise reducing headset enclosures
- Various Insert earphones models
- B81 High Output Bone Conductor
- Pediatric Headset (AC or BC)
- MDS software licence
- Quick-SIN test licence
- Silent cabin cables
- Free field loudspeaker
- Additional patient response pushbutton

Resonance makes no warranty, nor assumes any legal liability or responsibility for the accuracy, typing errors or mistakes, correctness or completeness of any information in this datasheet. The information in this datasheet was correct to the best of our knowledge at the time of printing.